

DBLV-2SF

Features


1. Body of the ball valve is made of stainless steel.
2. Full bore type ball valve.
3. Built-in thermal protector and torque protector.
4. The IP rating is IP67.



Specifications

Model	DBLV-2SF
Nominal size	15 - 100A
Application fluid	Steam, air, water, oil and other non-dangerous fluids
Connection	JIS 10K RF flanged ASME Class 150 flanged EN PN16 flanged
Maximum pressure	According to the pressure-temperature rating
Maximum temperature	
Valve material	Stainless steel
Seat material	PTFE
Voltage	15A - 25A: AC85V - AC265V 32A - 100A: AC220V (contact us for 100V and 200V)
Frequency	50/60Hz
Ambient temperature	-25 to 70 °C
Operation	ON-OFF, 90° bi-directional rotation
Manual operation	Possible

Pressure and Temperature Rating



Dimensions (mm) and Weight (kg)

Nominal size	L		H	Weight		
	JIS 10K ANSI 150lb	EN PN16		JIS 10K	ANSI 150lb	EN PN16
15A	108	130	191	3.1	2.8	3.3
20A	117	150	196	3.5	3.1	4
25A	127	160	215	5.1	4.1	5.6
32A	140	180.3	275	8.1	7	9.1
40A	165	200	298	10	9.4	11
50A	178	230	306	12.1	12	13.7
65A	190	290	431	24.2	24.1	26.5
80A	203	310	448	29.4	29.7	32.3
100A	229	350	462	35.6	39.8	40.1

